

FORTUS GEOGRID WALL



FORTUS GRAVITY WALL



FORTUS SQUARE FOOT



CAPS



CORNERS



CONCRETE / ASPHALT SWALE



CLAY OR IMPERVIOUS SWALE



NOTE: CONCRETE CORE FILL MIN 3 UNITS DEEP ALONG THE FULL LENGTH OF WALL WITH A 4.0FT MIN LENGTH GEOGRID AT THE SECOND LAYER.

WIND LOADS AND LATERAL LOADS HAVE NOT BEEN CONSIDERED. COSULT A QUALIFIED ENGINEER

FENCE IN BLOCK



NOTE: SONOTUBES ARE PLACED DURING CONSTRUCTION. DISTANCE FROM FACE OF WALL & DEPTH OF SONOTUBE VARY

WIND LOADS AND LATERAL LOADS HAVE NOT BEEN CONSIDERED. COSULT A QUALIFIED ENGINEER

FENCE W/ SONOTUBE



LEVELING PAD



LEVELING PAD STEP UP



TOP OF WALL ELEVATION



OUTSIDE CORNER



INSIDE CORNER



INSIDE CURVE



OUTSIDE CURVE

SECURELUG CONNECTION

General Notes

These preliminary details are intended solely to act as an aid when designing a wall. This drawing should not be used for final design or construction. Each site-specific wall should be certified and signed by a registered geotechnical engineer in the State or Province that it is being built. The accuracy and use of the details in this document are the sole responsibility of the user.

No.	Revision/Issue	Date

LIBERTYSTONE SINCE 1924 BEYOND THE BLOCK

Project Name and Address

Project	Sheet
Date	
Scale	

FNAME
REVDATE
USER